

VELA Wall Sconce

120v : **3-527-xx**

277v : **37-527-xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-20 Polished Nickel



-22 Oiled Bronze



-24 Satin Nickel



Alternative Position

LIGHT SOURCE 2 x 8.2W LED, 3000K, CRI 90

LUMINAIRE POWER 20.4W at 120V

RATED LIFE 60000 hr RL

OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K

LUMEN OUTPUT Delivered: 408 lm (LM-79)

INPUT VOLTAGE 120V or 277V

DRIVER OUTPUT 350 mA, 12W

DIMMING 0-10v & Phase (ELV) Dimming
50/60Hz 100% to 10% Dimming


CONSTRUCTION Plated Steel and Acrylic

DIFFUSER - Matte White Acrylic

FINISHES Polished Nickel (-20), Oiled Bronze (-22), Satin Nickel (-24)

MOUNTING 4" Octagonal J-Box*, 4"x4" J-Box*
*Deep J-Box (Required to house drivers)

STANDARDS ETL Dry/Damp listed, ADA compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 6.875"

H: 12.00"

Ext: 3.55"

M.C: 8.13" From top of fixture

Order example for standard fixture:

3-527-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-527-2724**

27: 2700K, 35: 3500K, 40: 4000K

